

MINI PORTABLE WINCH OPERATED LOADER

- Wheels 200mm dia. Bright zinc centres with roller bearings, solid rubber.
- Finish fully powder coated throughout. Colours orange and grey.
- All models with load retention frame and anchor points for retention straps.
- Protective hand grips are fitted as standard.
- Easy to operate in confined space.



REF	Cap Kg	Height lift mm	Overall dimensions mm			Fork dimensions mm			PRICE
			lowered ht	raised ht	width	width	projection	lowered ht	
ELP125 75	125	750	1130	1155	680	315	450	65	£585.62
ELP125 90	125	915	1195	1315	680	315	450	65	£602.49
ELP125 107	125	1070	1350	1510	680	315	450	65	£605.78
ELP125 122	125	1220	1500	1660	680	315	450	65	£627.76
ELP200 90	200	915	1195	1315	680	315	450	65	£614.60
ELP200 107	200	1070	1350	1510	680	315	450	65	£621.60
ELP200 122	200	1220	1500	1660	680	315	450	65	£652.40
RPP6	Detachable platform 485mm wide x 470mm long								£61.04
ELBS1	Foot operated braking system								£73.42



Platform



Braking System

EURO RANGE WINCH LOADER

- Two wheeled version for confined areas and can double up as a sack truck.
- Four wheeled with rear support version to handle bigger loads over longer distances.
- Optional braking system as detailed above.
- Standard supplied with a detachable steel platform.



Rear Support Open



Rear Support Closed

Type	Two Wheel Model		Rear Support Model
	VL125	VL200	VL200S
REF	VL125	VL200	VL200S
Max load capacity Kg	125	200	200
Max lift height mm	1070	1070	1070
Load centres mm	305	305	305
O/A dim. lowered height mm	1350	1350	1350
Fully raised height mm	1515	1515	1515
O/A dim. front to rear	730	790	790
Width mm	630	720	720
Platform width mm	485	575	575
Platform projection mm	470	470	470
Platform lowered height mm	70	70	70
Main rubber wheels mm	200	250	250
PRICE	£666.61	£708.40	£846.93