

## TELESCOPIC SCAFFOLD TOWER

The telescopic scaffold tower has a wide range of uses from maintenance work, decorating, through to light industrial tasks. The unique patented telescopic operation allows the tower to easily be transported, stored or erected.



- 7 adjustable platform heights from 0.33m up to 2m at 25mm increments offering a working height up to 4m.
- Operates as a podium with low level fixed height options of 33cm and 61cm.
- Fully erected in under 3 minutes saving down time and man hours.
- Can be transported in a small van or estate car.
- Comprises only two parts - tower and platform (no more leaving parts in the yard).
- Large folding aluminium work platform (1.40m x 0.7m) with climb through hatch.

- Integral telescopic hand and knee rail.
- Integral platform stabilisers.
- Integral stabilising legs with 5 optional positions and lockable castors.
- Single person operation.
- Minimal product footprint for ease of transportation and storage.
- Includes toeboards.
- Conforms to EN1004.
- Weight only 70kg.
- SWL 150 kg.



REF	PRICE
TELE/ST	£1200.00

## MOBILE SCAFFOLD TOWER

This mobile tower is approved to EN1004. The compact design can be stored and transported inside a small van and erected by one person in three minutes, with just the minimum of training! Gravity latches make rung-by-rung height adjustment effortless allowing the tower to be quickly adjusted to your desired height. Compact closed dimensions of 1.34m opens up to 3.1m x 2.0m platform.

- Safe working load of 150kg.
- Platform size: 1540 x 600mm.
- 250mm adjustable sections.
- Multi height adjustment up to 2.8m.
- Just two components: tower and folding anti-slip platform.
- No loose components to lose or leave behind.
- Fitted with four adjustable height 150mm dia locking castors.



- Foldable toe boards integrated to the platform.
- Stabilisers are millimetre adjustable for uneven ground.
- Folding hand and knee rails.
- Industrial strength design and components for frequent use.
- Platform height: 2800mm.
- Overall height: 3850mm.

REF	WITH STABILISERS		WITHOUT STABILISERS		PRICE
	O/A width mm	O/A length mm	O/A width mm	O/A length mm	
3010-036	840	1600	2050	2340	POA