



SIDE TILTING WORK POSITIONER

The tilt facility allows up to 20° in either direction. Supplied as standard with parking brake and foot protectors. Manual pump lift operation.

- Capacity 800kg.
- Manual lift/tilt.
- Max fork height 920mm.
- Min fork height 88mm.
- Fork dimensions 1150mm x 540mm.
- Net weight 210kg.

Our expert says

The tilt reduces operator fatigue

REF	PRICE
CTM-T	£1410.00



MINI STACKER

- Lightweight design, very easy to operate by hand winch.
- Suitable for supermarket, office, warehouse, narrow area etc.
- Adjustable fork.
- Conforms to EN1757-1.

REF		PM120
Capacity	kg	120
Lifting height	mm	1050
Min fork height	mm	95
Fork width	mm	adjustable 345-485
Individual fork width	mm	50
Fork length	mm	400
Load wheel	mm	Ø50 x 20
Steering wheel	mm	Ø200/50-140
Net weight	kg	31
PRICE		£710.50



Our expert says

Ideal for restricted access and spaces



ML100S



ML100SC

Our expert says

The perfect workmate for all types of jobs

MANUAL MINI LIFTER

The Mini Lifters are available in a standard or counterbalanced model. The latter can manoeuvre up close against a lifting point without the obstruction of wheel arms coming into contact with anything.

- 100kg capacity.
- Lift heights: 1500/1600mm.
- Hand pulley winch lift operation.
- Wheel brakes.
- Push/pull handle.
- Mesh protective load guard.
- Large range of lifting tool accessories available to customise the Mini Lifter to suit specific lifting tasks.
- Both models can be fitted with lifting jibs, clamps, reel holder, glass panel holder, crane arm, platform, roller platform, spur pole or stainless steel lifting accessories.

REF		ML100S	ML100SC
Capacity	kg	100	100
Lifting min/max	mm	1500	1600
Max height	mm	1750	1920
Rollers	N/ø mm	2/60 x 20	2/80 x 30
Wheels	N/ø mm	2/100 x 30	2/150 x 40
Lifting speed	N. giri	30	31
Weight	kg	57	250
PRICE		£2835.00	£3445.50