


SEMI ELECTRIC LIFT STACKER



Service friendly assembly of hydraulics, electrics and batteries. Large battery on 135Ah/12v, for many working hours per charging.

The MS Range has a compact design and small turning radius with the largest battery as standard. This gives many working hours per charging and high lifting/lowering speeds. Easy and smooth steering makes the stackers safe and easy to operate. Therefore the MS Range is the perfect choice for high productivity requirements in confined spaces. Three lifting heights 1600, 2400 and 3300mm. Nylon wheels only. Capacity is 1000Kg.

The two high lift models have a welded and reinforced chassis, duplex 2 stage lifting mast with C section profiles, dual chains and single lift cylinder, maintenance free bushings and sealed bearings (RS) in lift mast, fork carriage and wheels. Separate hydraulic system with protected motor, pump, valves and tank. This gives a long and trouble free lifetime.

REF		MS1016	MS1024	MS1033
Lifting Mast		Simplex 1-stage	Duplex 2-stage	Duplex 2-stage
Capacity	Kg	1000	1000	1000
Load centre	mm	600	600	600
Lift height, min-max	mm	85-1600 (free lift)	85-2450	85-3300
Fork width, outer-inner	mm	540-160	540-160	540-160
Fork length	mm	1150	1150	1150
Lifting speed, no load-load	mm/s	120-95	120-95	120-95
Lifting motor	W	800	800	800
Battery	Ah/v	135/12	135/12	135/12
Charger	Ah/v	15/12	15/12	15/12
Steer wheels	mm	ø180x50	ø180x50	ø180x50
Load wheels	mm	ø80x70 (single)	ø180x70 (single)	ø180x70 (single)
Turning radius (outside)	mm	1600	1600	1600
Dimension (LxWxH)	mm	1820x800x2130	1820x800x1800	1820x1090x2225
Weight	Kg	420	460	550
PRICE		£2248.50	£2392.50	£2488.50

MS1024

FULLY ELECTRIC STACKER

The FE Range has electric travel and electric lift. There is a choice of 1200Kg or 1500Kg capacity and lift heights from 1600mm - 3300mm.

- CE conformity and EN1757-1:2001.
- Curtis Electronic Control System.
- Power pack and drive wheel system manufactured in Europe.
- Ergonomic controls and tiller system.
- Polyurethane wheels and load rollers.

REF		FE1216	FE1529	FE1531	FE1533
Capacity	Kg	1200	1500	1500	1500
Lifting height	mm	1600	2900	3100	3300
Min fork height	mm	90			
Load centre	mm	600			
Fork length	mm	1150			
Fork width	mm	540			
Travelling speed	Km/h	Without load 5.5. With full load 4.8.			
Lifting speed	mm/s	Without load 144. With load 95.			
Lowering speed	mm/s	Without load 150. With full load 65.			
Overall length LxW	mm	2710 x 1080			
Closed/open H	mm	2090/2244	2025/3544	2125/3744	2225/3944
Battery (service free)		200/24 AH/V			
Battery charger		20/24 A/V			
Front roller	mm	78 x 700			
Rear roller	mm	150 x 75			
Drive wheel	mm	250 x 80			
Net weight	Kg	614	692	705	714
PRICE		£5775.00	£6780.00	£7125.00	£7425.00

