

# medium & heavy duty electric stackers

A superb range of fully electric stackers. The medium duty machines are intended for arduous applications and the heavy duty models are suitable for the most demanding types of work. All trucks are CE marked and comply with all current legislation. Comprehensive warranty and after sales service provided.

## MEDIUM DUTY STACKERS

- Capacity 1000Kg.
- Lift heights 920mm + 1610mm.
- Medium duty battery for 4 hours continuous work.
- Single mast for ease of use.
- Optimum driving qualities and manoeuvrability.
- Straddle legs, adjustable forks, side tilting forks available.

REF	CLC10.09	CLC10.16
Capacity Kg	1000	1000
At load centre mm	600	
Wheels	Polyurethane	
Lift height mm	920	1610
Lowered height forks mm	90	
Overall height mm	1970	1970
Mast configuration	Single	
Battery V/Ah	12/60	
<b>PRICE</b>	<b>£2208.00</b>	<b>£3793.62</b>



## HEAVY DUTY STACKERS

- Capacity 1200Kg.
- Lift height 2820mm, special orders: 3600mm + 2900mm full free lift.
- High quality hydraulic pump assures very little noise, maximum efficiency and durability.
- Lift limit switch operates at maximum lift height to shut off pump motor.
- Electromagnetic braking that is spring applied and electronically released.
- The CURTIS electronic controller provides plenty of low end torque while increasing the motor and battery life.
- Polyurethane wheels used throughout.

REF	CLC12.29	CLC12.29FFL	CLC12.36
Capacity Kg	1200		
At load centre mm	600		
Wheels	Polyurethane		
Lift height mm	2820	2820	3520
Freelift mm	158	1490	158
Lowered mast height mm	1946	1946	2296
Extended mast height mm	3276	3276	3976
Mast configuration	Duplex		
Battery V/Ah	24/210	12/210	12/210
<b>PRICE</b>	<b>£4755.48</b>	<b>£6052.68</b>	<b>£5173.62</b>



## HEAVY DUTY STACKERS

- Capacity 1600Kg and 2000Kg.
- Lift heights from 1600mm - 3600mm.
- Duplex and Triplex mast configuration allows good sight through the mast uprights.
- Ergonomic drive controls.
- Heavy duty traction battery for 8 to 9 hours continuous work even when negotiating inclines.
- Smooth stepless drive controls.

REF	CLC15.29	CLC15.36FFL	CLC15.46FFL	CLC15.50FFL
Capacity to full lift height Kg	1400	850	1100	500
At load centre mm	600	600	600	600
Wheels	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Lift height mm	2900	3600	4600	5000
Freelift mm	160	160	160	160
Optional freelift mm	150	1780	1505	1660
Closed mast height mm	1700	2300	2100	2480
Open mast height mm	2800	4070	5115	5520
Mast configuration	Duplex	Duplex	Duplex	Duplex
Battery V/Ah	24/280	24/280	24/280	24/280
<b>PRICE</b>	<b>£7544.46</b>	<b>£7606.56</b>	<b>£8757.48</b>	<b>£8894.10</b>

