

Counterbalanced stackers are used when it is not suitable to use either straddle wheel armed stackers or conventional narrow wheel arms. The pallet may not be suitable for lifting by certain stackers or the area of operation may be tight on space. Counterbalanced stackers can solve that problem. They can also be used to load and unload onto mezzanine floors when stackers with wheel arms cannot get close enough to the load/unload point.

- CE marked and compliant.
- Ergonomic drive controls with smooth stepless facility.
- Optional battery/charger capacities.
- Vast range of attachments and extras available.
- Comprehensive warranty, after sales and maintenance services provided.



COMPACT COUNTERBALANCED STACKER

- Capacity 600Kg (to lift height 2500mm).
- Lift heights 2500mm or 3000mm.
- High visibility Duplex mast.
- Optional extras: sideshift forks and tilting mast.

REF	CSLC06.25	CSLC06.30
Capacity to 1600mm Kg	600	
Capacity to full lift height	500	400
At load centre mm	500	
Wheels	Polyurethane	
Lift height mm	2500	3000
Closed mast height mm	1800	2095
Open mast height mm	2920	3580
Battery V/Ah	24/240	
PRICE	£10877.10	£10936.90

COMPACT COUNTERBALANCED STACKER

- Capacity 1000Kg.
- Lift heights 2500mm, 3000mm and 4500mm.
- High visibility Duplex + Triplex mast.
- Power steering and tilting mast.
- Heavy duty traction battery for 8 to 9 hours continuous work.
- Optional extras: sideshift forks.

REF	CSPC10.25	CSPC10.30	CSPC10.45
Capacity to 2500mm Kg	1000		
Capacity to full lift height Kg	800	800	600
At load centre mm	500		
Wheels	Polyurethane		
Lift height mm	2500	3000	4500
Closed mast height mm	1800	2100	2100
Open mast height mm	2920	3600	5150
Battery V/Ah	24/240	24/240	24/240
PRICE	£12365.60	£12608.70	£15314.00

HEAVY DUTY COUNTERBALANCED STACKER

- Capacity 1500Kg.
- Lift heights 2500mm, 3000mm and 4500mm.
- High visibility Duplex + Triplex mast.
- Built-in battery charger.
- Heavy duty traction battery for 8 to 9 hours continuous work even when negotiating inclines.
- Optional extras: sideshift forks and tilting mast.

REF	CSPC15.25	CSPC15.30	CSPC15.45
Capacity Kg	1500		
Capacity to full lift height Kg	1200	1100	900
At load centre mm	500		
Wheels	Polyurethane		
Lift height mm	2500	3000	4500
Freelift mm	160		
Closed mast height (h2) mm	1600	2100	2100
Open mast height (h3) mm	2920	3600	5150
Battery V/Ah	24/240	24/240	24/240
PRICE	£14276.60	£14485.90	£16754.40