

ECONOMY RANGE OF MOBILE SCISSOR LIFT TABLES

These scissor lift tables are ideal for use within machine workshops and loading bays. The units take the strain out of loading and unloading items from elevated levels. The units are fitted with an overload relief valve and a top of stroke bypass valve. They are elevated by a pump action foot pedal and smoothly lowered by a hand operated release trigger.

- Units comply to European Standards: SL150Y + SLD35Y - EN1570:1980, SL300Y + SL500Y - EN1570:1998, CE marked.
- Footbrakes fitted.
- Handles supplied knock down for ease of transport.

SL300Y



SLD35Y



SL150Y



REF	Cap Kg	Platform size	Lift height	Closed height	Pedal strokes	Castor size & type	Weight Kg	PRICE
SL150Y	150	800x450mm	740mm	225mm	25	100mm dia PVC on nylon	49	£385.02
SLD35Y	350	980x500mm	1300mm	348mm	55	127mm dia poly on steel	115	£573.11
SL300Y	300	850x500mm	900mm	340mm	32	127mm dia poly on steel	87	£491.60
SL500Y	500	850x500mm	900mm	340mm	45	127mm dia poly on steel	91	£522.05

LIFT TABLES WITH ZINC FINISH

- Top quality engineered zinc galvanised finish. Designed for clean environments.
- Single and double scissor versions.
- Foldable handles.

- Foot pump crank or battery models in capacities of 200, 400, 500 & 1000Kg.
- Rear wheels have rotational and directional locks. All wheels fitted with toe guards.
- Ideal for clean work areas.
- Conforms to EN1570.

REF	Capacity Kg	Max height mm	Min height mm	Length mm	Width mm	Platform mm	Height adjustment			Weight Kg pack excl	PRICE
							Power	Battery	Charger		
TZ303	200, Foot pump	920	320	1150	650	900x600	Foot pump	—	—	65	£1215.78
TZ503	500, Foot pump	920	320	1150	650	900x600	Foot pump	—	—	75	£1489.02
TZ503B	500, Battery	920	320	1150	650	900x600	0.8 kW	12V 24Ah	1.5A/230V	90	£2544.72
TZ1000B	1000, Battery	920	320	1230	800	1000x800	0.8 kW	12V 24Ah	1.5A/230V	150	£3647.34
TZD203	200, Foot pump	1620	450	1150	650	900x600	Foot pump	—	—	85	£1773.30
TZD203B	200, Battery	1620	450	1150	650	900x600	0.8 kW	12V 24Ah	1.5A/230V	100	£2800.02
TZD400B	400, Battery	1620	450	1230	800	1000x800	0.8 kW	12V 24Ah	1.5A/230V	200	£3776.50



POWERED ARM LIFT WITH TILT

Lifts the load with parallel arms and includes a tilting facility +5° to -40°. 'ALTU' and 'UE' models have a shaped platform for lifting pallets and trolleys directly from the ground. If a conveyor is required the height of the back edge can be manufactured to suit (standard height = 229mm). Pre-drilled holes for installing an auto-rise stop on the platform.

REF	Capacity Kg	Lift stroke mm	Lowest height mm	Platform Length		Platform Width		Lifting time secs	kW	Weight Kg pack excl	PRICE
				Ext mm	Int mm	Ext mm	Int mm				
ALT750*	750	820	235	1300	-	800	-	18	0.75	300	£4483.70
ALT1500	1500	820	235	1300	-	800	-	16	0.75	320	£5293.60
ALT1500U*	1500	820	235	1380	1200	1540	1050	16	0.75	360	£5778.50
ALT1500UE*	1500	820	236	1380	1200	1340	850	16	0.75	350	£5851.30
ALT3000GB	3000	820	238	1380	1200	1780	1250	24	0.75	460	£6871.80

* Remote power pack with cover. The alt-lifts must be securely fixed to the ground with expander bolts or similar.

