

U SHAPE SCISSOR LIFT TABLE

- 'U' shaped top platform.
- 'U' shaped table are specially for handling pallets, no need for a pit or load.
- They are manufactured to all European safety standards including EN1570-1999.
- Remote power pack with pedestal and controls, protected to IP54.
- Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.
- 24V control box with Up and DOWN buttons and emergency stop.
- External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed.
- Hose burst safety valve to stop the lift table lowering in case of hose breakage.
- Removable lifting eyes to facilitate handling and installation of the lift table.
- Oil-less bushings on pivot points.
- Quick assembly joint for oil hose.

Note: Clearance for pallet truck access is 585mm wide.

REF		HU600	HU1000	HU1500
Cap Kg		600	1000	1500
Max height H	mm	860	860	860
Collapsed height h	mm	85	85	105
Platform LxW	mm	1450x985	1450x1140	1600x1180
Lift time	sec	25-35	25-35	30-40
Power pack		380V/50Hz, AC1.1kw	380V/50Hz, AC0.75kw	380V/50Hz, AC1.5kw
Net weight	Kg	207	280	380
PRICE		£2898.55	£3081.25	£3182.75



LOW PROFILE SCISSOR LIFTS U AND E SHAPED



U and E shaped lifts specially designed for efficient handling of pallets. Designed to suit Euro type, free entry or two way pallets - no bottom board on the side used to access the pallet with a pallet truck. All models have remote power pack with cover. Specialist advice on request.

REF	TUB600*	TUB600H*	TUL1000*	TUL2000*
Cap Kg	600	600	1000	2000
Lift stroke mm	720	970	820	820
Lowest Ht mm	80	80	80	100
Length Ext mm	1450	1450	1350	1700
Length Int mm	1200	1200	1100	1350
Width Ext mm	900	900	1055	1145
Width Int mm	580	580	735	585
Lift time secs	13	19	13	23
kW	0.75	0.75	0.75	0.75
Weight Kg	210	210	260	370
Shape	E	E	U	U
PRICE	£3997.86	£3867.50	£3985.80	£5020.60

Ref 600H and 1000H must be securely bolted to ground

LOW PROFILE LIFT TABLES

- Action's low profile lifts have a mechanism with a very low closed height to eliminate the need for pit installation.
- Power pack is remote with cover provided.
- Special sizes on request.
- 'H' models must be securely fixed to floor.

REF	Capacity Kg	Lift stroke mm	Lowest height mm	Length mm	Width mm	Lifting time secs	kW	Weight Kg pack excl	PRICE
TCR500	500	630	80	900	600	9	0.75	100	£3012.54
TCB600	600	720	80	1500	900	13	0.75	210	£3607.50
TCB600H	600	970	80	1500	900	19	0.75	210	£3707.60
TCL1000*	1000	820	80	1350	800	13	0.75	280	£3892.20
TCL1000B*	1000	970	80	1350	1000	13	0.75	292	£4072.90
TCL1000GB*	1000	820	80	1350	1270	13	0.75	315	£4578.60
TCL2000*	2000	820	100	1350	800	23	0.75	400	£4919.20
TCL2000B*	2000	820	100	1350	1000	23	0.75	425	£5020.60

